



PRODUCT INFORMATION



PNZ FLOOR LACQUER

- Semi gloss
- Water-based

Suitable for: For the renovation of parquet, cork and wood floors as well as stairs. Of limited suitability for exotic woods with low oil content (test application). PNZ FLOOR LACQUER is environmentally compatible and therefore environmentally friendly. ONZ FLOOR LACQUER is hard-wearing and durable, protects against moisture and is resistant against many household chemicals.

- Application/ Treatment:**
- Final sanding step of the wood surface prior to priming with 120 grain.
 - Surface must be clean, residue-free.
 - Application temperature from $>15^{\circ}\text{C}$, $<30^{\circ}\text{C}$.
 - Acts differently on differing surfaces. Trial coats are absolutely necessary.
 - Stir contents well before and during use.
 - Watch out for potential gluing of sides.
 - When using several containers with different lot numbers, mix together in larger container.
 - Possible application as primer or topcoat.
 - **Initial application no earlier than 14 days after installation of flooring.**

Priming: Apply twice using the spatula method (cross coating). Drying time approximately 1 hour. Apply once using the rolling and painting method. Drying time approximately 2 hours. Do not sand after priming.

Topcoat: Apply 2-3 times using the rolling and painting method. Slightly sand using 120 or 150 grain prior to last coat. Drying time after topcoats 2-4 hours each. May be walked on after 8 hours using caution. Final hardness and full load capacity after approximately 10 days. The drying times presume normal conditions (20°C and 55% relative humidity). Higher humidity and lower temperatures may significantly lengthen the drying time. Only use in well ventilated areas (no draft).

Maintenance: Moist mopping with PNZ WOOD FLOOR SOAP. Regular maintenance with PNZ FLOOR POLISH or PNZ ORGANIC FLOOR WAX.

Use: Spatula method approximately 70 g/m^2 per coat. Rolling or painting method approximately $100\text{-}120\text{ g/m}^2$ per coat. Total coat min. 360 g/m^2 .

please turn over 

Our technical advice in written form is given in good faith and on the basis of experiments, but it is only non-binding advice and does not release you from the obligation to test the products supplied by us as to their suitability for the particular purpose. Application, use and processing of the products outside our direct control are entirely your responsibility. Naturally we guarantee consistent quality of our products corresponding to the original sample. With release of new product information the previous information loses validity.



PNZ-Produkte GmbH
D-85110 Kipfenberg · Eichstätter Straße 2-4a
Phone +49(0)8465-17380 · Fax +49(0)8465-3616
E-Mail: info@pnz.de · Internet: www.pnz.eu

A love of wood

natural protection and care
www.pnz.eu

